

JUST ADD WATER



20 kg

PROSTRENGTH[®] RAPID SET CONCRETE

HARDENS IN 30 MINUTES

40 MPa*

40MPa* - Twice the strength of standard Rapid Set
Load bearing after 24 hours
Faster project turnaround without compromising strength

MADE
Right Here

**CEMENT
AUSTRALIA[®]**



PROFESSIONAL
FENCING



LOAD BEARING
POSTS



RETAINING
WALLS



SIGN
INSTALLATION

plus restumping, decking
and gate posts

HARDENS
IN 30 MINS

PROSTRENGTH[®] RAPID SET CONCRETE

When mixed to directions and cured adequately, the product is capable of:

- ✓ Combined **rapid setting** and **fast strength gain**
- ✓ **Twice as strong** as standard Rapid Set Concrete



Suitable for around the home and building site, concrete footings for professional fencing, gates and road sign posts, retaining walls, sporting grounds equipment that demand high early strength and rapid setting.

40MPa*
in 28 days!

Compressive Strength Maturity



*40MPa – When tested using Australian Standard Methods (AS1012, Methods 8.1 & 9), this product will achieve up to 40MPa compressive strength at 28 days.

- 
PROFESSIONAL FENCING
- 
LOAD BEARING POSTS
- 
RETAINING WALLS
- 
SIGN INSTALLATION

Coverage:
Approximately 110 x 20kg bags are required per cubic metre.

Limitations:

- Concrete is not recommended for use with aluminium posts or poles unless these are primed or sealed according to the post manufacturers' recommendation.
- Extreme temperatures will impact set time of PROStrength® Rapid Set Concrete. Not recommended for use below 10°C.

Tips:

- It is important that you are prepared to complete the project quickly as this product has fast setting properties.
- When using for posts, pre wet the hole if dry.
- Hot temperatures will impact set times, avoid working in direct sunlight.
- Clean all tools and equipment with water without delay after use.

Item Code 17763
Cement Australia
 PROStrength
 Rapid Set Concrete 20kg



Product Disclaimer

Recommendations regarding the use of this product are to be taken as a guide only. If in doubt contact Cement Australia Pty Limited ("Cement Australia") or seek professional advice. To the extent permitted by law, Cement Australia excludes all implied warranties, conditions and guarantees imposed by legislation. Cement Australia excludes all liability for loss, damage or injury arising from use of the product (i) otherwise than in accordance with the recommendations of (ii) for purposes other than those for which it is ordinarily acquired. For all other loss, damage or injury arising from the use of this product, to the extent permitted by law Cement Australia's liability is limited, at its discretion, to refunding the cost of the product or resupplying the product or equivalent product.

